

A. Typical Applications

Item	Parameter
Description	Live Cable Connector
Uses	The live Cable Connector should only be used by approved operatives adhering to company regulations and work practices while using appropriate safety equipment and clothing. For use on live cables up to 480VAC 60/50Hz.

B. Live Cable Connector Assembly

Item	Parameter
Construction	Polycarbonate
Weight	1.5lbs (0.7kg)
Dimension	6.3in(L) x 3.1in(W) x 2.2in(H) (160mm x 80mm x 56mm)
Power Supply Options	Transmitter provides power in, the output leads from the separation filter can be connected to conductors carrying up to 480V AC
Compliance/Approvals	- Complies with European standard CE (Directive 2004/108/EC) • EN 61326-1 - EN 61010-1 EN 61010-2 - Complies with FCC Rules Part 15 • CATIII • UL94 HB

C. Operational

Item	Parameter
Frequency Range	8.192kHz, 32.768kHz, 8.44kHz SIS
Compatible With Transmitter	Loc-10Tx, Loc-10TxSIS, Loc-5Tx, Loc-1Tx and vScan Tx

D. Environmental

Item	Parameter
Temperature Range	Operating : -4°F to 122°F (-20°C to 50°C) Storage : -40°F to 140°F (-40°C to 60°C)
Shipping Weight	2.1lbs (0.94kg)
Shipping Dimension	10in(L) x 9.3in(L) x 3.3in(L) (253mm x 237mm x 84mm)

E. Warranty

Item	Parameter
Warranty	12 months

Disclaimer: Product and accessory specification and availability information is subject to change without prior notice.

Vivax-Metrotech Corp. (Headquarters)

Your Vivax-Metrotech Dealer:
Indepth Utility Solutions LLC
 4100 Greenbriar Dr., Suite 240
 Stafford, TX 77477
 281-969-8530
www.indepthUS.com
info@indepthUS.com

