



VIVAX
METROTECH

indepthTM
UTILITY SOLUTIONS
281-969-8530

VM-810

Technical Specifications V2.2



VIVAX
METROTECH

A. Description and Typical Applications

Item	Parameter	
Model Number	VM-810 Receiver	VM-810 Transmitter
	VX213-01	VX213-02
Description	Single high-frequency locator receiver and transmitter	
Uses	Locating & pinpointing the position of buried pipes and cables	

B. Receiver Characteristics

Item	Parameter	
Construction	<ul style="list-style-type: none"> - High impact thermoplastic (ABS) injection molded housing - Retractable aluminum antenna tube 	
Weight	3.1lbs (1.4kg)	
Dimensions	Collapsed: 22in(L) x 8.3in(W) x 11in(H) (560mm x 210mm x 280mm) Extended: 31.1in(L) x 8.3in(W) x 11in(H) (790mm x 210mm x 280mm)	
Display Type	Black & white TFT 2.7" LCD WQVGA display (400 x 240 pixel)	
Receiver Antennas	3 x Peak antennas, 1 x compass antenna	
Batteries	2 x D-Cell alkaline batteries	
Battery Life	Typically 65 hours continuous use at 70°F (21°C)	
Environmental	IP54 and NEMA 4	
Manufacturing	Designed and manufactured per ISO 9001:2015	
External Connectors	<ul style="list-style-type: none"> - 1 x 3.5mm Headphone jack - 1 x Mini USB socket for software update - 1 x 4 pin Accessory jack 	
Temperature Range	Operating: -4°F to 122°F (-20°C to 50°C)	
Compliance/Approvals	<ul style="list-style-type: none"> - Complies with European standard CE (Directive 99/5/EC) <ul style="list-style-type: none"> • EN 55011 • EN 61000-4-2 • EN 61000-4-3 • EN 61000-4-8 	<ul style="list-style-type: none"> - Complies with FCC Rules Part 15 <ul style="list-style-type: none"> • CFR 47 Part 15: 2006
What's In the Box	<ul style="list-style-type: none"> - VM-810 Receiver - Hard case - Mini-USB cable 	<ul style="list-style-type: none"> - 2 x Alkaline D-Cell batteries - User handbook

Compatible Accessory Options	<ul style="list-style-type: none"> - D22 Sonde, 8ft/2.4m depth range – 83kHz - D38 Sonde, 16.3ft/5m depth range – 83kHz - D64 Sonde, 26ft/8m depth range – 83kHz - Headphones with 3.5mm jack
-------------------------------------	---

C. Receiver Operational

Item	Parameter								
Information Displayed	<ul style="list-style-type: none"> - Signal strength: Numeric value - Distance sensitive Left/Right Centerline offset needle indicator - Compass: +/- 90° line direction indicator - Battery indicator - Depth and current reading 								
Audio Indication	<ul style="list-style-type: none"> - Tones for Left or Right - Fading when close to centerline - Silence when centered or signal is too weak 								
Configuration	<p>Easy One-button operation:</p> <ul style="list-style-type: none"> - Automatic backlight control - Short press – On - Long press – Off - Short press when the unit is switched On – Depth and Current reading 								
Operating Frequencies	83.1kHz (83,077.5 Hz)								
Operating Modes	<ul style="list-style-type: none"> - Peak locate - Sonde 								
Gain / Scaling Control	Automatic Gain control								
Performance Using Single Undistorted Signal Source	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Trace accuracy:</td> <td>- Distance Sensitive Left/Right Guidance™</td> </tr> <tr> <td>Current measurement accuracy:</td> <td> <ul style="list-style-type: none"> - 5% of actual current – up to 10ft (3m) - 10% of actual current – up to 20ft (6m) </td> </tr> <tr> <td>Depth measurement accuracy:</td> <td> <ul style="list-style-type: none"> - 10 feet (3m): +/-5% or 2" - 20 feet (10m): +/-10% </td> </tr> <tr> <td colspan="2">Depth range: Dependent on the strength of signal radiating to the locator</td> </tr> </table>	Trace accuracy:	- Distance Sensitive Left/Right Guidance™	Current measurement accuracy:	<ul style="list-style-type: none"> - 5% of actual current – up to 10ft (3m) - 10% of actual current – up to 20ft (6m) 	Depth measurement accuracy:	<ul style="list-style-type: none"> - 10 feet (3m): +/-5% or 2" - 20 feet (10m): +/-10% 	Depth range: Dependent on the strength of signal radiating to the locator	
Trace accuracy:	- Distance Sensitive Left/Right Guidance™								
Current measurement accuracy:	<ul style="list-style-type: none"> - 5% of actual current – up to 10ft (3m) - 10% of actual current – up to 20ft (6m) 								
Depth measurement accuracy:	<ul style="list-style-type: none"> - 10 feet (3m): +/-5% or 2" - 20 feet (10m): +/-10% 								
Depth range: Dependent on the strength of signal radiating to the locator									
Compatible with Transmitters	VM-810, 810 classic, 810DX								

A. Transmitter Characteristics

Item	Parameter
Construction	High impact thermoplastic (ABS) injection molded housing
Weight	2.95 lbs (1.34kg)
Dimension	14.6in(L) x 4.5in(W) x 3.3in(H) (370mm x 115mm x 85 mm)
Power Options	Standard battery pack - using 6 x alkaline "D" cells
Battery Life	At 70°F (21°C) - continuous use Output Power Alkaline 1 watt > 60 hours
Environmental	IP54 and NEMA 4
Manufacturing	Designed and manufactured per ISO 9001:2015
External Connectors	3-pin XLR connection socket
Temperature Range	Operating : -4°F to 122°F (-20°C to 50°C) Storage : -40°F to 140°F (-40°C to 60°C)
Compliance and Approvals	<ul style="list-style-type: none"> - Complies with European standard CE (Directive 99/5/EC) <ul style="list-style-type: none"> • EN 55011 • EN 61000-4-2 • EN 61000-4-3 • EN 61000-4-8 - Complies with FCC Rules Part 15 <ul style="list-style-type: none"> • CFR 47 Part 15
What's In the Box	<ul style="list-style-type: none"> - VM-810 Transmitter - 1 x direct connection lead (XLR plug with two cables each 10ft (3.5m) long with crocodile clips) - 1 x T shaped ground stake - Transmitter shoulder strap - 4 x Alkaline D-Cell batteries
Compatible Accessories Options	<ul style="list-style-type: none"> - 2in (50mm) transmitter clamp - 4in (100mm) transmitter clamp - 5in (125mm) transmitter clamp - Live Plug Connector - Live Cable Connector - Ground Extension Spool - Telco Clip Connection Lead

B. Transmitter Operational

Item	Parameter
Location Modes	- Induction mode – applies signal inductively using the internal antenna

	<ul style="list-style-type: none"> - Direct connection mode - applies signal directly to the cable by clipping one output lead to the cable, the other to an independent ground - Clamp mode – applies signal using an inductive clamp (toroid) that is placed around the target cable <p>* Modes are selected automatically when accessories are plugged in. * Default mode (no accessories) is induction.</p>
Transmitting Frequency by Mode	- Induction mode / Direct connection mode / Clamp mode: 83.1kHz (83,077.5Hz)
Transmitting Mode	In accordance with FCC part 15:
Power output	<ul style="list-style-type: none"> - 1 watt – in High output level - 1/3 watt – in Low output level
Maximum Output Voltage	Maximum output voltage = 60V RMS
Maximum Output Current	Maximum output current = 150mA RMS constant power
Output Protection	Output protected against accidental connection to up to 240V AC (50/60Hz)
Audio indication	<ul style="list-style-type: none"> - Connection quality – variable beep rate sound showing the better signal applied - Low battery warning
Controls	Use pushbuttons to select: <ul style="list-style-type: none"> - Power button: On / Off - Output level button: Low / High - Audio button: Off / Low / High
Compatible Receivers	VM-810, 810DX, 810 classic

C. Shipping and Packaging (Full Kit)

Item	Parameter
Shipping Weight	18.7lbs (8.5kg) (Full Kit)
Shipping Dimension	22.7in(L) x 13.8in(W) x 4.3in(H) (577mm x 350mm x 109mm) (estimation)

D. Warranty

Item	Parameter
Warranty	Receiver and Transmitter -12 month (Limited warranty)

Disclaimer: Product and accessory specification and availability information are subject to change without prior notice.