

RT 200

Technical data sheet

Device data	
Dimensions (W x D x H)	115 x 115 x 68 mm 115 x 115 x 244 mm with aerial
Weight	430 g (with aerial)
Material	polycarbonate (housing)
Product variants	country-specific

Certificates	
Certificate	FCC, CE, IC
Marking	everywhere apart from USA: Contains: 70TX-D2 only USA: Contains: 70TX-D, FCC-ID:PUX70TX-D

Device elements	
Signal light	1 LED red/green for operating status 3 LEDs green for filter
Interface	internal (USB)
Processor	DSP, 16 bit / 120 MHz
Operation	membrane keypad

Operating conditions	
Operating temperature	-20 °C – +60 °C
Storage temperature	-25 °C – +50 °C (briefly +60 °C)
Humidity	15% – 90% r.h. non-condensing
Protection rating	IP65 IP67 with aerial
Non-permitted operating environments	in potentially explosive areas

Power supply	
Power supply	lithium ion battery (rechargeable) [1357-0002], built-in
Operating time, minimum	> 8 h (23 °C)
Battery power	24 Wh
Charging time	< 6 h
Charging temperature	0 °C – +45 °C
Charging voltage	12 V
Charging current	1.2 A
Charger	AC/DC adapter L (charge in case)

Measurement	
Filter	<ul style="list-style-type: none"> - 3 bandpasses: 0 – 500 Hz, 0 – 4000 Hz, 200 – 4000 Hz - Notch filter
Sampling rate	16 bit, 48 kHz
Measurement ranges	0 – 1 Vrms
Sensitivity	automatic amplification: 163 levels (-17.25 – +89 dB)

Data transmission	
Transmission frequency	<ul style="list-style-type: none"> - international: 433.9 /434,4 MHz - France: 444.5500 /444,9875 MHz - UK: 458.5125 /458,7875 MHz - USA: 468.5 /469,6 MHz
Radio range	> 500 m
Transmission bandwidth	5 kHz <ul style="list-style-type: none"> - 0 – 4 kHz: NF - 4 – 5 kHz: Control signals
Communication	analogue
Power	500 mW

GPS	
Accuracy	2.5 m CEP
Aerial	integrated

Additional data	
Shipping instructions	UN 3481: lithium ion batteries contained in equipment or lithium ion batteries packed with equipment net weight of battery/batteries: 0.098 kg

Assignment	
System components of	SeCorr system, SeCorrPhon system
For use with	universal microphone UM 200, hydrophone HY 200

Subject to technical changes.




 4310 FM 2218 Rd
 Richmond, TX 77469
Corp: (281) 969-8530
info@indepthUS.com
www.indepthUS.com