



VIVAX
METROTECH

indepthTM
UTILITY SOLUTIONS
281-969-8530

Remote Antenna

Technical Specifications V2.4



A. Typical Applications

Item	Parameter
Description	Single-channel stethoscope
Uses	To aid in cable identification, particularly in situations where multiple cables are bundled together or in the same cable tray.

B. Characteristics

Item	Parameter
Construction	POM (Polyoxymethylene)
Weight	0.3lbs (0.125kg)
Dimension	1.5-inch (Dia.) x 2.2-inch (L) (39mm x 55mm)
Cable Length	53-inches (1.3m)
Environmental	IP54
Manufacturing	ISO 9001:2015
External Connectors	– 1 x 8-pin pull release plug – ¼ -Inch/ 6.35mm female threads
Temperature Range	Operating: -4°F to 122°F (-20°C to 50°C) Storage: -40°F to 140°F (-40°C to 60°C)
What's in the Box	Remote Antenna Quick Guide
Compatible Accessory Options	Clamp extension rod (with ¼"/6.35mm stud)

C. Operational

Item	Parameter
Frequency Range	512Hz to 200kHz, SD, and SiS
Compatible Receivers	vLoc3 Series Receivers. SD mode is an option and must be ordered or retrofitted in most vLoc3 receivers. SD mode is not available in the vLoc3-9800 or vLoc3-Cam. SiS mode is only available in the vLoc3-5000 receiver when used with the SiS transmitter.

D. Shipping and Packaging

Item	Parameter
Shipping Weight	0.45lbs (0.203kg)
Shipping Dimensions	9.8-inch(L) x 3.7-inch(W) x 2.4-inch(H) (250mm x 95mm x 62mm)

E. Warranty

Item	Parameter
Warranty	12 months

Disclaimer: Product and accessory specifications and availability information are subject to change without prior notice.

Your Local Distributor:



4310 FM 2218 Rd
Richmond, TX 77469

Corp: (281) 969-8530

info@indepthUS.com

www.indepthUS.com

