



VIVAX
METROTECH

indepthTM
UTILITY SOLUTIONS
281-969-8530

VM-510FFL+ A-frame

Technical Specifications V1.5



A. Description and Typical Applications

Item	Parameter
Model Name	VM-510FFL+
Model Number	VX218-04
Description	Combination cable locator and ground fault locator
Applications	Identifying the position of a cable and locating insulation faults to ground and pipeline coating defects that are in contact with the ground

B. Characteristics

Item	Parameter
Construction	Carbon fiber/ reinforced glass fiber/ high impact thermoplastic (ABS) construction
Weight	4.23lbs (1.92kg)
Dimension	28.7in(H) x 25.2(W) x 2.9in(T) (728mm x 640mm x 74mm)
Display	1.28" 128 x 128 black and white dot matrix LCD
Power Supply	Six x AA alkaline batteries. Also compatible with Six NiMH size AA batteries
Battery life	Alkaline: typically, 60 hours continuous use at 70°F (21°C) NiMH: typically, 2300mAh will provide 45 hours continuous use at 70°F (21°C)
Environmental	IP 54 and NEMA 4
Manufacturing	Designed and manufactured per ISO 9001:2015
External Connectors	Mini-USB for maintenance and software upgrades.
Temperature Range	Operating: -4°F to 122°F (-20°C to 50°C) Storage: -40°F to 140°F (-40°C to 60°C)
Approvals	CE/FCC
What's In the Box	VM-510FFL+ Receiver USB Cable Soft carry bag Rubber spike covers
Compatible Transmitters	Loc and Loc3 series transmitters with FF modes, VM-550FF, VM560FF

C. Operational

Item	Parameter
Information Displayed	Mode, Frequency, Peak/Null/Left/Right, depth, and current. Fault signal strength and direction. Battery condition and Speaker volume setting
Operating Frequency	8kFF (8Hz/8.192kHz with 2.67Hz phase modulation) or FF (3Hz/6Hz/8.192kHz)
Cable Locate Sensitivity	10uA at one-meter depth
Fault Locate Sensitivity	Typically, it can detect 2MΩ at one-meter depth.
Accuracy	Depth Accuracy - From 4" to 10' (100mm to 3M), accuracy is +/- 5% of the depth.
Audible	The speaker indicates Left/Right by pulsed/continuous tone.

D. Shipping and Packaging

Item	Parameter
Shipping Weight	9.4lbs (4.25kg)
Shipping Dimension	31.5in(L) x 27.8in(W) x 4.5in(H) (800mm x 705mm x 115mm)

E. Warranty

Item	Parameter
Warranty	<ul style="list-style-type: none"> - Two Years - Optional extended warranty available

F. Firmware Updates

Item	Parameter
Firmware	Firmware can be upgraded using a PC with a USB port. Programs & locator software are available via the MyLocator3 app.

Disclaimer: Product and accessory specification and availability information are subject to change without prior notice.

indepthTM
UTILITY SOLUTIONS

4310 FM 2218 Rd
Richmond, TX 77469

Corp: (281) 969-8530

info@indepthUS.com

www.indepthUS.com

