

vCamMX-2

Mini-Inspection System

- Seven-hour battery life
- Free video streaming app
- On-screen distance, date and time
- Record to USB with SD card backup
- One-touch recording and image capture

The vCamMX-2 Mini-camera system is versatile and compact at an affordable price. Easily inspect lines from 1-1/2 to 4" (38 to 100mm), choosing three interchangeable camera heads and two pushrod lengths. The vCamMX-2 mini-camera features a three-frequency sonde, locatable pushrod, distance counter, internal rechargeable batteries, and a built-in voice-over microphone. Record directly to the USB drive while creating a backup copy on the SD card or connect to the VMC app by Wi-Fi and record to the tablet or smartphone.

The vCamMX-2 uses the latest HD and HDR technology to produce clear, crisp videos and images in bad lighting situations. The free VMC app allows instant file sharing through the tablet or smartphones file-sharing options.

Internal microphone for audio commenting over recording videos

WIFI - 30' / 10m Range



8" daylight viewable display

Video out through RCA composite socket
Export distance out and video via the mini-USB port

Automatic backup of videos and pictures to SD Card

Large keypad usable while wearing gloves

Internal rechargeable battery provides seven-hours of battery life

Locatable three-frequency sonde and traceable pushrod

Available interchangeable camera heads

Field-serviceable spring assembly

D20-HD 0.78" / 20mm self-leveling camera

D26-HDR 1" / 26mm self-leveling camera

Lightweight, durable carbon-fiber pushrod drum

Optional 0.70" / 18mm Camera

D18-HD 0.70" / 18mm non-leveling camera

- One-year warranty covers entire system
- Extended warranty is available
- Camera exchange program for out of warranty camera heads

Backed by Vivax-Metrotech's superior dealer network, customer service and service centers.

www.indepthUS.com | info@indepthUS.com

Camera Heads

	D26-HDR	D20-HD	D18-HD
Application:	2 to 4"/50 to 101mm	1-1/2 to 4"/38 to 101mm	1-1/2 to 3"/38 to 75mm
Dimensions:	1.02" x 1.41"/26mm x 35.9mm	0.79" x 1.27"/20mm x 32.2mm	0.73" x 0.71"/18.6mm x 18.1mm
Lighting:	103 Lumens	73 Lumens	69 Lumens
Resolution:	720p	1080p	1080p
Construction:	Stainless-steel housing with scratch-resistant Sapphire lens		
Self-leveling:	Yes	Yes	No
Environmental:	11 BAR	11 BAR	11 BAR
Focus point:	6"/15cm	4"/10cm	4"/10cm
Field of view:	114°	90°	90°

vCamMX-2 System

Dimensions:	22.8" (L) x 15" (W) x 28" (H)/58cm x 38cm x 70cm
Shipping Weight:	100 ft./30m: 42 lbs./19kgs. 150 ft./45m: 45 lbs./21kgs. (Includes control module, accessory kit, charger, reel with pushrod, spring assembly and insert sleeve)
Construction:	High impact ABS control module, stainless-steel tubular frame, with a carbon-fiber drum
Display:	8"/20cm Daylight viewable 800 x 600 TFT LCD display
Battery life:	Eight-hours with sonde off, seven-hours with sonde on
Environmental:	Water resistant to IP65 (light shower with lid closed)

Type-MX Mini-Reel

vCamMX-2 can be purchased as a complete all-in-one unit with the control module mounted to the reel, or purchase the reel separately to use with the vCam-6 control module.



Type-MX Reel with 100ft/30m or 150ft/45m of pushrod



vCam-6 Control Module



Interconnect plugs into the vCam-6 control module



D26-HDR, D20-HD and D18-HD camera heads

Sonde Locators



VM-540 and vLoc3-Cam

Popular Accessories



D18-HD camera



MX Drip bag



vCam Mobile Controller App

Your Local Distributor:



4310 FM 2218 Rd
Richmond, TX 77469

Corp: (281) 969-8530

info@indepthUS.com

www.indepthUS.com

Please visit our website for full product specifications.

Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

Tel: +1-408-734-1400

www.vivax-metrotech.com



V1.6