



VIVAX
METROTECH

indepthTM
UTILITY SOLUTIONS
281-969-8530

vLoc3-DM

Technical Specifications V1.3



VIVAX
METROTECH

A. Description and Typical Applications

Item	Parameter
Model Name	vLoc3-DM
Model Number	VX222-01
Description	Pipeline defect mapper receiver
Intended Use	<ul style="list-style-type: none"> - Locating and pinpointing coating defects on buried pipelines - Profiling the CP current distribution on a pipeline network - Identification of short circuits from pipelines to other structures - Long distance pipeline location - Locating & pinpointing the position of buried pipes and cables

B. Characteristics

Item	Parameter
Construction	High impact thermoplastic (ABS) injection molded housing
Weight	5.7lbs (2.6kg)
Dimensions	12.3in(L) x 4.6in(W) x 30.8in(H) (312mm x 116mm x 783mm)
Display Type	High-Visibility Color Display, 4.3"/10cm with 480 x 272 resolution
Receiver Antennas	<ul style="list-style-type: none"> - Two sets of Omnidirectional Antennas, each comprising: <ul style="list-style-type: none"> • Two Compass Antennas • Two Horizontal antennas • Two Vertical antennas - Low Frequency Field Sensor Foot
Batteries	<ul style="list-style-type: none"> - Six x AA Alkaline batteries - Rechargeable custom Lithium-ion batteries with 100-240V AC mains charger
Battery Life	<ul style="list-style-type: none"> - Alkaline – typically 12 hours intermittent use at 70°F (21°C) - Lithium-ion – typically 27 hours intermittent use at 70°F (21°C) <p>* With backlight activated, battery life varies with temperature, re-charging cycles are approximately 500 times the life cycle</p>
Environmental	IP65 and NEMA 4
External Connectors	<ul style="list-style-type: none"> - Accessory Socket – to change the internal batteries and attach accessories - Mini-USB socket for data transfer and programming

Temperature Range	<ul style="list-style-type: none"> - Operating: -4°F to 122°F (-20°C to 50°C) - Storage: -40°F to 140°F (-40°C to 60°C) 	
Compliance and Approvals	<ul style="list-style-type: none"> - Complies with European standard CE (Directive 99/5/EC) <ul style="list-style-type: none"> • EN 55011 • EN 61000-4-2: A1 & A2 • EN 61000-4-3 • EN 61000-4-8: A1 • ETSI EN 300 330-2 	<ul style="list-style-type: none"> • ETSI EN 301 489-1 • ETSI EN 301 489-3 - Complies with FCC Rules Part 15 <ul style="list-style-type: none"> • CFR 47 part 2 • CFR 47 Part 15
Manufacturing	Designed and manufactured per ISO 9001:2015	
What's In the Box	<ul style="list-style-type: none"> - vLoc3-DM Receiver - Attachable Low Frequency Field Sensor Foot - Factory-fitted GPS Module - Bluetooth module - Custom lithium-ion battery pack - 100-240V AC mains charger - Six x AA Alkaline battery holder - Mini-USB data transfer cable - User handbook - Padded carry bag 	
Compatible Accessories	<ul style="list-style-type: none"> - A-frame fault and holiday locator - Remote Antenna (Stethoscope) - Vehicle Charging DC Lead - Range of Sondes (waterproof, self-contained transmitters for use in nonmetallic pipes & ducts) 	

C. Operational

Item	Parameter
Information Displayed	Information screen: <ul style="list-style-type: none"> - Real-time horizontal accuracy in 2DRMS - Distance from last logged current point - Current direction - DM current warning - GPS coordinates - Current on the line

	<ul style="list-style-type: none"> - Depth reading - Logging options - Enter graph screen option <p>Status Bar Information:</p> <ul style="list-style-type: none"> - Antenna configuration: Peak, Peak with arrows, Broad Peak, Null, Delta Null, Omni Directional Peak, Omni Directional Broad - Line location - depth & current measurement - Battery condition - Speaker volume - Bluetooth and GNSS status - Low frequency field sensor connected <p>Locate screen (Classic display):</p> <ul style="list-style-type: none"> - Distance from last recorded reading (if GPS is active) - Signal strength - moving bar graph & numeric value - Bar graph color-coded indicating distortion level - Peak level indicator - Proportional left/right indication - Compass: full 360°-line direction indicator - Gain level (in dB) - Frequency selected - Configuration menus including GNSS status and data logging transfer status - Depth and current - Warnings (if activated) - Plug and play automatic recognition of accessories - Accessory specific custom screens <p>Customer definable start-up screen</p>
Locate Perspectives	<ul style="list-style-type: none"> - Classic Locate – moving bar graph with a value showing signal strength - Vector Locate Screen – fully automatic locate including offset, depth and locate uncertainty - Transverse Graph Screen - visual assessment of locate quality and distortion - Plan View Screen – fully automatic graphical representation of the cable position independent of cable direction, including depth/current and locate uncertainty. - Sonde Locate Screen – directing arrow to move to the Sonde position along the polar axis
Configuration	<p>Intuitive setup menu enables user to configure:</p> <ul style="list-style-type: none"> - Setup frequency selection to toggle by “f” pushbutton - Setup location mode selection to toggle by “m” pushbutton

	<ul style="list-style-type: none"> - Setup screen views selection to toggle by long press “<i>m</i>” pushbutton - Units of measure (feet/meters) - Sound – normal or modulated pitch - Language - Continuous depth/current options - Loudspeaker level - Backlight brightness - Bluetooth pairing - Warnings (Excessive Tilt, Overhead Signal, Shallow Cable, Signal Overload) - Auto shut down – configurable to power down at five minutes, ten minutes, or never
Data Logging	<ul style="list-style-type: none"> - 50 million record internal storage - Data can also be transferred for storage, via cellular connectivity, into the cloud using the Vivax-Metrotech application, VM MAP - All parameters stored at each location including depth, current, date, time, mode, gain setting, frequency, locate uncertainty, longitude, latitude, and height above sea-level
Data Transfer	<ul style="list-style-type: none"> - Via the Vivax-Metrotech "MyLocator3" software application available free of charge from www.vivax-metrotech.com. Data can be saved in csv, klm, shp, txt, xls and xlsx formats. The transfer is via a USB cable connection from the locator to the host computer. <p>Or</p> <ul style="list-style-type: none"> - Cellular transfer to the VM Map Cloud (Vivax-Metrotech Cloud) via the VM Map mobile app
Operating Frequencies	<ul style="list-style-type: none"> - Configurable frequencies from 98Hz to 200 kHz - ELF) 3Hz/6Hz/98Hz - (ELF) 4Hz/8Hz/98Hz - 3Hz/6Hz/512Hz - 4Hz/8Hz/512Hz - 4Hz/8Hz/640Hz - 3Hz/6Hz/640Hz - Power 50Hz and 60Hz - Radio 22.7kHz, 10kHz bandwidth - Signal Direction” (SD) - enhanced frequency indicating the direction of the transmitter’s signal. SD-USA: 256Hz/512Hz, SD-EUROPE: 320Hz/640Hz
Operating Modes	<ul style="list-style-type: none"> - Peak, Peak with arrows, Broad Peak - Null, Delta Null - Omni Directional Peak, Omni Directional Broad
Gain Control	<ul style="list-style-type: none"> - Manual gain using "+" or "-" keys - One-touch of "+" or "-" keys rescales to 60% of the bar graph scale

	<ul style="list-style-type: none"> - In Vector Screen, "+" and "-" keys act as zoom feature to keep target utility in view - In the Transverse Graph screen, the "+" key saves the screen graph, "-" key clears the screen 	
Accuracy	Locate pinpointing accuracy:	<ul style="list-style-type: none"> - Over 9ft (3m) – 5% of depth - Up to 9ft (3m) – 3% of depth
	Depth measurement accuracy:	+/- 5% of depth
	Current measurement accuracy:	<ul style="list-style-type: none"> - 5% of actual current – over 9ft (3m) - 3% of actual current – up to 9ft (3m)
	* Performance rated using a single undistorted signal source	
Compatible Transmitters	Loc3-25Tx, Loc-150Tx	

D. Shipping and Packaging

Item	Parameter
Shipping Weight	15.7lbs (7.1kg)
Shipping Dimension	14.1in(L) x 11in(W) x 29.8in(H) (358mm x 279mm x 756mm)

E. Warranty

Item	Parameter
Warranty	<ul style="list-style-type: none"> - Two years - Optional extended warranty available

F. Software Updates

Item	Parameter
Software	The software can be upgraded using a PC with a USB port. Program updates & locator software updates are available via the free MyLocator3 app.

Disclaimer: Product and accessory specification and availability information are subject to change without prior notice.



4310 FM 2218 Rd
Richmond, TX 77469

Corp: (281) 969-8530

info@indepthUS.com

www.indepthUS.com